



## Immersion Heater Controller

SEHAZB-HEAT-CONT-3



DEVICE CONTROL

### Maximizes self-consumption by storing excess energy as hot water

- Immersion heater controller adjusts the power supplied to the heater based on available PV power (up to 3kW)
- Seamless integration with all SolarEdge inverters
- Wireless communication between the inverter and Immersion Heater Controller via ZigBee
- Simple wall mount installation
- Suitable for powering purely resistive loads only

	SEHAZB-HEAT-CONT-3	UNITS
<b>ELECTRICAL SERVICE</b>		
Operating Voltage Range	207 - 253	Vac
AC Frequency	50	Hz
Supported Grids	L / N / PE	
Maximum Supported Load Size	3	kW
Maximum Load Current Rating	13	A
Minimum Output Power	2% of load rating	
Load Type	Resistive	
Efficiency	> 97	%
<b>COMMUNICATION</b>		
Supported Communication Protocol	ZigBee Home Automation	
Nominal Transmit Power	10	dBm
Operating Frequency Range	2.4 - 2.5	GHz
Outdoor (LOS) Range	400	m
Indoor Range*	50	m
<b>STANDARD COMPLIANCE</b>		
Radio	ETSI EN 300 328 V 1.8.1, ETSI EN 301 489-1, ETSI EN 301.489-17	
Safety	EN-60335-1, EN60335-2-21	
Immunity	EN 61000-6-3, EN 55014-1, EN 55014-2	
Emissions	EN 61000-6-2, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1	
<b>INSTALLATION SPECIFICATIONS</b>		
Dimensions (H x W x D)	277 X 309 X 70.5	mm
Weight	3.9	kg
Operating Temperature Range	-5 to +40	°C
Cable Gland Diameters	2 glands 6-12, 2 glands 4-8	mm
Terminal Block Minimum Wire Cross Section	2.5	mm <sup>2</sup>
Protection Rating	IP20	
Mounting Type	Wall mount	

\* Approximate values. May differ depending on specific installation conditions

### SolarEdge System with Immersion Heater Controller

